

COMMONWEALTH OF AUSTRALIA

Ministerial Exemption Instrument No. 6 of 2013

Customs Tariff (Anti-Dumping) Act 1975

I, BOB BALDWIN, Parliamentary Secretary to the Minister for Industry, under subsection 8(7) and 10(8) of the *Customs Tariff (Anti-Dumping) Act 1975*, hereby exempt the goods described in Attachment 1 (the Goods) from:

- interim dumping duty and dumping duty, and
- interim countervailing duty or countervailing duty,

as I am satisfied that a Tariff Concession Order under Part XVA of the *Customs Act 1901* in respect of the goods is in force.

This instrument commences on the 4th day of September 2013.

Dated this day of 2013

BOB BALDWIN

Parliamentary Secretary to the Minister for Industry

CURRENT Tariff Concession Order (TCO) for tariff classification 7210.49.00 and 7210.30.00

All goods meeting the description detailed below for the current TCOs are eligible for an exemption from dumping duties and countervailing duties under Ministerial Exemption Instrument No. 6 of 2013.

TCO 1316842

STEEL, flat rolled, non-alloy, electrolytically plated OR coated with zinc, in coils, having ALL of the following:

- (a) yield strength NOT less than 110 MPa and NOT greater than 240 MPa;
- (b) tensile strength NOT less than 260 MPa;
- (c) elongation NOT less than 37%;
- (d) coating mass NOT less than 36 g/m² and NOT greater than 90 g/m² on each side;
- (e) in ANY of the following sizes:
 - (i) thickness 0.70 mm and width 980 mm; (ii) thickness 0.70 mm and width 1 160 mm;
 - (iii) thickness 0.70 mm and width 1 250 mm; (iv) thickness 0.70 mm and width 1 520 mm; (v) thickness 0.70 mm and width 1 640 mm;
 - (vi) thickness 0.80 mm and width 960 mm;
 - (vii) thickness 0.80 mm and width 1 160 mm; (viii) thickness 0.80 mm and width 1 370 mm; (ix) thickness 0.80 mm and width 1 600 mm;
 - (x) thickness 0.90 mm and width 950 mm

For the purposes of this Order, tolerances allowable for specification (e) are:

- (a) thickness +/- 10%
- (b) width +/- 1%

TC1316841

STEEL, flat rolled, non-alloy, hot dipped zinc coated, in coils, having ALL of the following:

- (a) yield strength NOT less than 110 MPa and NOT greater than 280 MPa;
- (b) tensile strength NOT less than 260 MPa;
- (c) elongation NOT less than 37%;
- (d) coating mass NOT less than 45 g/m² and NOT greater than 100 g/m² on each side;
- (e) in ANY of the following sizes:
 - (i) thickness 0.60 mm and width 1 670 mm;
 - (ii) thickness 0.65 mm and width 960 mm;
 - (iii) thickness 0.65 mm and width 1 075 mm;
 - (iv) thickness 0.65 mm and width 1 160 mm;
 - (v) thickness 0.65 mm and width 1 240 mm;
 - (vi) thickness 0.65 mm and width 1 425 mm
 - (vii) thickness 0.65 mm and width 1 430 mm;
 - (viii) thickness 0.65 mm and width 1 445 mm;

- (ix) thickness 0.65 mm and width 1 630 mm;
- (x) thickness 0.65 mm and width 1 730 mm;
- (xi) thickness 0.70 mm and width 810 mm;
- (xii) thickness 0.70 mm and width 840 mm;
- (xiii) thickness 0.70 mm and width 850 mm;
- (xiv) thickness 0.70 mm and width 890 mm;
- (xv) thickness 0.70 mm and width 896 mm;
- (xvi) thickness 0.70 mm and width 1 390 mm;
- (xvii) thickness 0.70 mm and width 1 400 mm;
- (xviii) thickness 0.70 mm and width 1 410 mm;
- (xix) thickness 0.70 mm and width 1 440 mm;
- (xx) thickness 0.70 mm and width 1 460 mm;
- (xxi) thickness 0.70 mm and width 1 540 mm;
- (xxii) thickness 0.70 mm and width 1 590 mm;
- (xxiii) thickness 0.70 mm and width 1 650 mm;
- (xxiv) thickness 0.70 mm and width 1 655 mm;
- (xxv) thickness 0.75 mm and width 1 600 mm;
- (xxvi) thickness 0.75 mm and width 1 695 mm;
- (xxvii) thickness 0.75 mm and width 1 760 mm;
- (xxviii) thickness 0.80 mm and width 680 mm;
- (xxix) thickness 0.80 mm and width 1 185 mm;
- (xxx) thickness 0.80 mm and width 1 300 mm;
- (xxxi) thickness 0.80 mm and width 1 370 mm;
- (xxxii) thickness 0.80 mm and width 1 325 mm;
- (xxxiii) thickness 0.80 mm and width 1 545 mm;
- (xxxiv) thickness 0.80 mm and width 1 600 mm;
- (xxxv) thickness 0.80 mm and width 1 695 mm;
- (xxxvi) thickness 0.80 mm and width 1 760 mm;
- (xxxvii) thickness 0.80 mm and width 1 840 mm;
- (xxxviii) thickness 0.90 mm and width 950 mm;
- (xxxix) thickness 0.90 mm and width 1 530 mm;
- (xl) thickness 0.90 mm and width 1 800 mm;
- (xli) thickness 1.20 mm and width 1 730 mm;
- (xlii) thickness 1 20 mm and width 1 770 mm

For the purposes of this Order, tolerances allowable for specification (e) are:

- (a) thickness +/- 10%
- (b) width +/- 1%