

COMMONWEALTH OF AUSTRALIA

***Ministerial Exemption Instrument No. 4 of 2013***

***Customs Tariff (Anti-Dumping) Act 1975***

I, IAN MACFARLANE, Minister for Industry, under subsection 8(7) of the *Customs Tariff (Anti-Dumping) Act 1975*, hereby exempt the goods described in Attachment 1 (the Goods) from:

- interim dumping duty, and
- dumping duty,

as I am satisfied that a Tariff Concession Order under Part XVA of the *Customs Act 1901* in respect of the good is in force.

This instrument commences on the 28th day of December 2012.

Dated this 19<sup>th</sup> day of November 2013

IAN MACFARLANE  
Minister for Industry

## Attachment 1

**CURRENT Tariff Concession Orders (TCO) for tariff classification 7208.26.00**

All goods meeting at least one of the descriptions detailed below for the current TCOs are eligible for an exemption from dumping duties under Ministerial Exemption Instrument No. 4 of 2013.

**TC 1349335**

STEEL, flat rolled, iron OR non-alloy steel, hot rolled, pickled, not coated, in coils, complying with Japanese Industrial Standard G3134 (JIS G3134) grade SPFH590 OR Japanese Industrial Standard G3113 (JIS G3113) grade SAPH440, having ALL of the following:

- (a) yield strength NOT less than 265 MPa and NOT greater than 600 MPa;
- (b) tensile strength NOT less than 440 MPa;
- (c) total elongation NOT less than 18% and NOT greater than 46%;
- (d) in EITHER of the following sizes:
  - (i) thickness 3.20 mm and width 1 034 mm;
  - (ii) thickness 3.20 mm and width 1 350 mm

For the purposes of this Order, tolerances allowable for specification (d) are:

- (a) thickness +/- 10%
- (b) width +/- 1%

**CURRENT Tariff Concession Orders (TCO) for tariff classification 7208.27.00**

All goods meeting at least one of the descriptions detailed below for the current TCOs are eligible for an exemption from dumping duties under Ministerial Exemption Instrument No. 4 of 2013.

**TC 1349331**

STEEL, flat rolled, iron OR non-alloy steel, hot rolled, pickled, not coated, in coils, complying with Japanese Industrial Standard G3131 (JIS G3131), grades SPHC OR SPHD, having ALL of the following:

- (a) yield strength NOT less than 175 MPa and NOT greater than 325 MPa;
- (b) tensile strength NOT less than 270 MPa;
- (c) total elongation NOT less than 35% and NOT greater than 53%;
- (d) in ANY of the following sizes:
  - (i) thickness 1.40 mm and width 1 050 mm;
  - (ii) thickness 1.40 mm and width 1 330 mm;
  - (iii) thickness 1.60 mm and width 1 228 mm;
  - (iv) thickness 1.80 mm and width 1 025 mm

For the purposes of this Order, tolerances allowable for specification (d) are:

- (a) thickness +/- 10%
- (b) width +/- 1%

**TC 1349332**

STEEL, flat rolled, iron OR non-alloy steel, hot rolled, pickled, not coated, in coils, complying with Japanese Industrial Standard G3134 (JIS G3134) grade SPFH590 OR Japanese Industrial Standard G3113 (JIS G3133) grade SAPH440, having ALL of the following:

- (a) yield strength NOT less than 265 MPa and NOT greater than 600 MPa;
- (b) tensile strength NOT less than 440 MPa;
- (c) total elongation NOT less than 18% and NOT greater than 46%;
- (d) in ANY of the following sizes:
  - (i) thickness 1.40 mm and width 1 150 mm;
  - (ii) thickness 2.00 mm and width 836 mm;
  - (iii) thickness 2.60 mm and width 1 120 mm;
  - (iv) thickness 2.60 mm and width 1 246 mm

For the purposes of this Order, tolerances allowable for specification (d) are:

- (a) thickness +/- 10%
- (b) width +/- 1%