National Measurement Institute




REFERENCE MATERIAL PRODUCT INFORMATION SHEET

NMIA D565: 6β-Hydroxymethandienone

Report ID: D565.2022.02 (Ampouled 180913)

Chemical Formula: C₂₀H₂₈O₃ Molecular Weight: 316.4 g/mol



Property value

Batch No.	CAS No.	Mass per ampoule
99-000016	33526-41-9	1001 ± 17 μg

IUPAC name: (6β,17β)-6,17-dihydroxy-17-methylandrosta-1,4-dien-3-one.

Expiration of certification: The property values are valid till 12 April 2027, i.e. five years from the date of re-certification provided the **unopened** material is handled and stored in accordance with the recommendations below. The material as issued in the unopened container and stored as recommended below should be suitable for use beyond this date, subject to confirmation of batch stability from the issuing body. The expiry date/shelf life does not apply to ampoules that have been opened. In such cases it is recommended that the end-user conduct their own in-house stability trials.

Description: The compound is supplied as a dried aliquot in a sealed ampoule under an atmosphere of argon. The reference material is intended for a single use to prepare a standard solution containing D565. This material was prepared by sourced from an external supplier, and certified for identity and purity by NMIA.

Intended use: This reference material is recommended for qualitative analysis only and is not intended for use as a calibrator. The material does not have certified reference material status as metrological traceability of the stated purity value to the SI unit for mass (kg) has not been established.


Instructions for use: Open the ampoule and carefully rinse the interior at least three times with a suitable organic solvent (e.g. methanol). This will transfer approximately $1001 \, \mu g$ of anhydrous 6β -hydroxymethandienone. The mass of analyte in each ampoule is calculated from the assigned purity of the bulk and the concentration of bulk material in a stock solution used to prepare the ampoules.

Recommended storage: When not in use, this material should be stored at or below 4 °C in a closed container in a dry, dark area.

Stability: At the recommended storage conditions this material has demonstrated stability for a period of five years. The long-term stability of the compound in solution has not been examined.

Homogeneity assessment: The homogeneity of the material was assessed using purity assay by HPLC with UV detection on seven randomly selected ampoules of the material. The material was judged to be sufficiently homogeneous at this level of sampling as the variation in analysis results between samples was not significantly different at a 95% confidence level from that observed on repeat analysis of the same sample.

Safety: Treat as hazardous substance. Use appropriate work practices when handling to avoid skin or eye contact, ingestion or inhalation of dust. Refer to the provided safety data sheet.



Dr Stephen R. Davies, Team Leader, Chemical Reference Materials, NMI. 1 November 2022

This report supersedes any issued prior to 1 November 2022.

NATA Accreditation No. 198 / Corporate Site No. 14214.

Legal notice: Terms and Conditions associated with the provision of this reference material can be found on the NMIA website.

Characterisation Report:

HPLC: Instrument: Shimadzu Binary pump LC-20AB, SIL-20A HT autosampler

Column: Alltima C-18, $5\mu m$ (4.6 mm × 150 mm)

Column oven: 40 °C

Mobile Phase: A = MilliQ water; B = Acetonitrile

0-8 min 30% B; 8-9 min 30-80% B; 9-14 min 80% B; 14-15 min 80-30% B, 15-22 min

30%B

Flow rate: 1.0 mL/min

Detector: Shimadzu SPD-M20A PDA operating at 248 nm

Relative peak area of the main component:

Initial analysis: Mean = 99.8%, s = 0.002% (7 ampoules in duplicate, September 2018) Re-analysis Mean = 99.8%, s = 0.003% (5 ampoules in duplicate, August 2019) Re-analysis Mean = 99.8%, s = 0.001% (5 ampoules in duplicate, April 2022)

The following analytical data was obtained on the bulk material subsequently used in the preparation of the ampoules.

Characterisation Report:

The identity was confirmed by a range of spectroscopic techniques, NMR, IR and MS. The purity value was obtained by mass balance from a combination of traditional analytical techniques, including HPLC with UV detection thermogravimetric analysis, Karl Fischer analysis and ¹H NMR spectroscopy. The purity value is calculated as per Equation 1

Purity = $(100 \% - I_{ORG}) \times (100 \% - I_{VOL} - I_{NVR})$

Equation 1

I_{ORG} = Organic impurities of related structure, I_{VOL} = volatile impurities, I_{NVR} = non-volatile residue.

Supporting evidence is provided by elemental microanalysis.

GC-FID: Instrument: Agilent 6890

Column: HP-1, 30 m \times 0.32 mm l.D. \times 0.25 μ m

Program: 220 °C (1 min), 10 °C/min to 280 °C, 20 °C/min to 300 °C (1 min)

Injector: 250 °C

Detector Temp: 320 °C

Carrier: Helium

Split ratio: 20/1

Relative peak area of the main component:

Initial analysis: Mean = 99.3%, s = 0.04% (10 sub samples in duplicate, February 1999) Re-analysis: Mean = 99.6%, s = 0.02% (7 sub samples in duplicate, June, 2008)

HPLC: Instrument: Shimadzu Binary pump LC-20AB, SIL-20 A HT autosampler

Column: Alltima C-18, 5μ m (4.6 mm × 150 mm)

Column oven: 40 °C

Mobile Phase: Acetonitrile/MilliQ water (30:70 v/v)

Flow rate: 1.0 mL/min

Detector: Shimadzu SPD-M20A PDA operating at 248 nm

Relative peak area of the main component:

Initial analysis: Mean = 99.8%, s = 0.01% (5 sub samples in duplicate, November 2010) Re-analysis: Mean = 99.8%, s = 0.003% (7 sub samples in duplicate, September 2018)

Thermogravimetric analysis: Volatiles content < 0.1% and non-volatile residue 0.3% mass fraction (June and

November 2015)

Karl Fischer analysis: Moisture content 0.16% mass fraction. (2 sub samples in AG solution, June 2008)

Moisture content 0.14% mass fraction (2 sub samples in AK solution, July 2008)

Moisture content 0.09% mass fraction (2 sub samples in AK solution, September 2018)

Spectroscopic and other characterisation data

GC-MS: Parent compound:

Instrument: Agilent 6890/5973

Column: HP Ultra 2, 17 m x 0.22 mm ID x 0.11 μm

Program: 140 °C (1 min), 8 °C/min to 250 °C, 30 °C/min to 300 °C (1 min)

Injector: 280 °C Transfer line temp: 300 °C

Carrier: Helium, 1.0 mL/min

Split ratio: 30/1

Tris-TMS derivative:

Instrument: Agilent 6890/5973

Column: HP Ultra 1, 17 m x 0.25 mm ID x 0.22 μ m Program: 180 °C (1 min), 12 °C/min to 310 °C (2 min)

Injector: 250 °C Transfer line temp: 300 °C

Carrier: Helium, 1.0 mL/min

Split ratio: 20/1

The retention times of the parent compound and *tris*-TMS derivative are reported along with the major peaks in the mass spectra. The latter are reported as mass/charge ratios and (in brackets) as a percentage relative to

the base peak.

Parent (14.9 min): 316 (M+, 6), 298 (27), 283 (32), 265 (30), 225 (40), 107 (100) m/z Tris -TMS (7.4 min): 532 (M+, 8), 519 (37), 518 (66), 517 (100), 229 (10), 73 (87) m/z

TLC: Conditions: Kieselgel 60F₂₅₄. Hexane/ethyl acetate/chloroform (15:10:5)

Single spot observed, $R_f = 0.30$. Visualisation with UV at 254 nm

IR: Instrument: FT-IR, Biorad WIN FTS40

Range: 4000-400 cm-1, KBr pellet

Peaks: 3497, 3390, 1661, 1620, 1452, 1401, 1048 cm⁻¹

¹H NMR: Instrument: Bruker ARX-500

Field strength: 500 MHz

Solvent: CDCl₃ (7.26 ppm)

Spectral data: δ 0.95 (3H, s), 1.18 (3H, s), 1.44 (3H, s), 4.52 (1H, t), 6.13 (1H, d),

6.18 (1H, dd), 7.05 (1H, d) ppm

Ethanol and dichloromethane estimated at 0.22% and 0.06% mass fraction

respectively were observed in the ¹H NMR

¹³C NMR: Instrument: Bruker ARX-500

Field strength: 126 MHz

Solvent: CDCl₃ (77.2 ppm)

Spectral data: δ 14.0, 20.3, 22.3, 23.3, 25.7, 30.8, 31.3, 38.8, 39.7, 43.7, 45.6, 49.8, 51.9, 73.7, 81.5,

125.6, 126.5, 157.6, 166.5, 186.8 ppm

Melting point: 227-229 °C

Microanalysis: Found: C = 75.9%; H = 9.0% (February, 1999)

Calculated: C = 75.9%; H = 8.9% (Calculated for $C_{20}H_{28}O_3$)