




CERTIFIED REFERENCE MATERIAL CERTIFICATE OF ANALYSIS

NMIA D870: Piperonal

Report ID: D870.2024.01

Chemical Formula: C₈H₆O₃

Molecular Weight: 150.1 g/mol



Certified value

Batch No.	CAS No.	Purity (mass fraction)
04-D-12	120-57-0	99.9 ± 0.3%

The uncertainty has been calculated according to ISO Guide 35 and is stated at the 95% confidence limit (k = 2).

IUPAC name: 1,3-Benzodioxole-5-carbaldehyde

Expiration of certification: The property values are valid till 5 January 2034, ten years from the date of re-certification provided the **unopened** material is handled and stored in accordance with the recommendations below. The material as issued in the unopened container and stored as recommended below should be suitable for use beyond this date, subject to confirmation of batch stability from the issuing body. The expiry date/shelf life does not apply to sample bottles that have been opened. In such cases it is recommended that the end-user conduct their own in-house stability trials.

Description: Off-white solid prepared by sourced from an external supplier and certified for identity and purity by NMIA. Packaged in amber glass bottles with a septum and crimped aluminium cap or screw top cap.

Intended use: This certified reference material is suitable for use as a primary calibrator.

Instructions for use: Equilibrate the bottled material to room temperature before opening.

Recommended storage: When not in use this material should be stored at or below 25 °C in a closed container in a dry, dark area.

Metrological traceability: The certified purity value is traceable to the SI unit for mass (kg) through Australian national standards via balance calibration. In the mass balance approach all impurities are quantified as a mass fraction and subtracted from 100%.

Stability: This material has demonstrated stability over a minimum period of ten years. The measurement uncertainty at the 95% confidence interval includes a stability component which has been estimated from annual stability trials. The long-term stability of the compound in solution has not been examined.

Homogeneity assessment: The homogeneity of the material was assessed using purity assay by GC-FID on ten randomly selected 1-2 mg sub samples of the material. The material was judged to be sufficiently homogeneous at this level of sampling as the variation in analysis results between samples was not significantly different at a 95% confidence level from that observed on repeat analysis of the same sample.

Safety: Treat as a hazardous substance. Use appropriate work practices when handling to avoid skin or eye contact, ingestion or inhalation of dust. Refer to the provided safety data sheet.

S. R. Davies

Dr Stephen R. Davies,
Team Leader,
Chemical Reference Materials, NMI.
9 January 2024

This report supersedes any issued prior to 9 January 2024.

NATA Accreditation No. 198 / Corporate Site No. 14214.

Legal notice: Terms and Conditions associated with the provision of this reference material can be found on the NMIA website.

Characterisation Report:

The identity was confirmed by a range of spectroscopic techniques, NMR, IR and MS. The certified purity value was obtained by mass balance from a combination of traditional analytical techniques, including GC-FID, thermogravimetric analysis, Karl Fischer analysis and ¹H NMR spectroscopy. The purity value is calculated as per Equation 1.

$$\text{Purity} = (100 \% - I_{\text{ORG}}) \times (100 \% - I_{\text{VOL}} - I_{\text{NVR}}) \quad \text{Equation 1}$$

I_{ORG} = Organic impurities of related structure, I_{VOL} = volatile impurities, I_{NVR} = non-volatile residue.

Supporting evidence is provided by elemental microanalysis.

GC-FID:	Instrument:	Agilent 6890N
	Column:	HP-1, 30 m × 0.32 mm I.D. × 0.25 μm
	Program:	60 °C (1 min), 10 °C/min to 120 °C, 20 °C/min to 300 °C
	Injector:	200 °C
	Detector Temp:	320 °C
	Carrier:	Helium
	Split ratio:	20/1
	Relative mass fraction of the main component:	
	Initial analysis:	Mean = 99.99%, s = 0.006% (10 sub samples in duplicate, June 2004)
	Re-analysis:	Mean = 99.99%, s = 0.003% (5 sub samples in duplicate, August 2006)
	Re-analysis:	Mean = 99.99%, s = 0.002% (5 sub samples in duplicate, September 2009)
	Re-analysis:	Mean = 99.99%, s = 0.003% (5 sub samples in duplicate, July 2014)
	Re-analysis:	Mean = 99.99%, s = 0.005% (5 sub samples in duplicate, July 2019)
	Re-analysis:	Mean = 99.99%, s = 0.001% (5 sub samples in duplicate, January 2024)

Karl Fischer analysis: Moisture content < 0.1% mass fraction (August 2006, August 2009, July 2014, May 2019 and January 2024)

Spectroscopic and other characterisation data

GC-MS:	Instrument:	HP 6890/5973
	Column:	ZB-5, 30 m × 0.25 mm I.D. × 0.20 μm
	Program:	60 °C (1 min), 10 °C/min to 250 °C (1 min)
	Injector:	220 °C
	Transfer line temp:	280 °C
	Carrier:	Helium
	Split ratio:	20/1
	The retention time of the parent compound is reported along with the major peaks in the mass spectrum. The latter are reported as mass/charge ratios and (in brackets) as a percentage relative to the base peak.	
	11.6 min:	151 (M ⁺ , 8), 150 (84), 149 (100), 121 (27), 91 (9), 63 (22), 62 (10) <i>m/z</i>
TLC:	Conditions:	Kieselgel 60F ₂₅₄ . Hexane/ethyl acetate (3/1) Single spot observed, R _f = 0.2-0.3. Visualisation with UV at 254 nm
IR:	Instrument:	Biorad FTS300MX FT-IR
	Range:	4000-400cm ⁻¹ , KBr pellet
	Peaks:	3330, 3000, 2920, 2852, 2795, 2044, 1863, 1679, 1599, 1488, 1449, 1256, 1096, 1037, 929, 815, 786 cm ⁻¹
¹ H NMR:	Instrument:	Bruker Gyro-300
	Field strength:	300 MHz
	Solvent:	CDCl ₃
	Spectral data:	δ 6.06 (2H, s), 6.91 (1H, d, <i>J</i> = 7.9 Hz), 7.31 (1H, d, <i>J</i> = 1.1 Hz), 7.39 (1H, dd, <i>J</i> = 1.5, 7.9 Hz), 9.79 (1H, s) ppm
¹³ C NMR:	Instrument:	Bruker Gyro-300
	Field strength:	75 MHz
	Solvent:	CDCl ₃
	Spectral data:	δ 102.0, 106.9, 108.3, 128.6, 131.9, 148.7, 153.1, 190.2 ppm
Melting point:		36 - 37 °C
Microanalysis:	Found:	C = 64.1%, H = 4.2% (July 2004)
	Calculated:	C = 64.0%, H = 4.0% (Calculated for C ₈ H ₆ O ₃)
Thermogravimetric analysis:		Non volatile residue < 0.2 % total mass fraction Volatile content not determined due to volatility of the material.