National Measurement Institute



REFERENCE MATERIAL PRODUCT INFORMATION SHEET

NMIA D616: 9α-Fluoro-17α-methyl-4-androsten-3α, 6β, 11β, 17β-tetrol

Report ID: D616.2024.01 (Ampouled 220818)

Chemical Formula: C₂₀H₃₁FO₄ Molecular Weight: 354.5 g/mol

HO HO OH

Property value

Batch No.	CAS No.	Mass per ampoule
99-S-24	148505-57-1	986 ± 26 μg

The uncertainty has been calculated according to ISO Guide 35 and is stated at the 95% confidence limit (k = 2).

IUPAC name: $(3\alpha,6\beta,11\beta,17\beta)$ -9-Fluoro-17-methylandrost-4-ene-3,6,11,17-tetrol

Expiration of certification: The property values are valid till 19 June 2027, three years from the date of certification provided the **unopened** material is handled and stored in accordance with the recommendations below. The material as issued in the unopened container and stored as recommended below should be suitable for use beyond this date, subject to confirmation of batch stability from the issuing body. The expiry date/shelf life does not apply to ampoules that have been opened. In such cases it is recommended that the end-user conduct their own in-house stability trials.

Description: The compound is supplied as a dried aliquot in a sealed ampoule under an atmosphere of argon. The reference material is intended for a single use to prepare a standard solution containing D616. The material was sourced from an external supplier and certified for identity and purity by NMI Australia.

Intended use: This reference material is recommended for qualitative analysis only and is not intended for use as a calibrator. The material does not have certified reference material status as metrological traceability of the stated purity value to the SI unit for mass (kg) has <u>not</u> been established.

Instructions for use: Open the ampoule and carefully rinse the interior at least three times with a suitable organic solvent (e.g. methanol). This will transfer approximately 986 \pm 26 μ g of anhydrous 9 α -fluoro-17 α -methyl-4-androsten-3 α , 6 β , 11 β , 17 β -tetrol. The mass of analyte in each ampoule is calculated from the assigned purity of the bulk and the concentration of bulk material in a stock solution used to prepare the ampoules.


Recommended storage: When not in use, this material should be stored at or below 4 °C in a closed container in a dry, dark area

Stability: In the absence of long term stability data the measurement uncertainty at the 95% coverage interval has been expanded to accommodate any potential change in the property value. The stability component has been estimated from stability trials conducted on similar materials by NMI Australia over the last ten years. The measurement uncertainty at the 95% confidence interval also includes a stability component determined from accelerated stability trials conducted at 40 °C and 75% humidity for 14 days

The long-term stability of the compound in solution has not been examined.

Homogeneity assessment: The homogeneity of the material was assessed using purity assay by UHPLC with UV detection on seven randomly selected ampoules of the material. The material was judged to be sufficiently homogeneous at this level of sampling as the variation in analysis results between samples was not significantly different at a 95% confidence level from that observed on repeat analysis of the same sample.

Safety: Treat as hazardous substance. Use appropriate work practices when handling to avoid skin or eye contact, ingestion or inhalation of dust. Refer to the provided safety data sheet.



Dr Stephen R. Davies, Team Leader, Chemical Reference Materials, NMI. 8 July 2024

This report supersedes any issued prior to 8 July 2024.

NATA Accreditation No. 198 / Corporate Site No. 14214.

Legal notice: Terms and Conditions associated with the provision of this reference material can be found on the NMIA website.

Ampouled 18 August 2022

Characterisation Report:

HPLC: Instrument: Thermo Scientific Vanquish Flex

Column: ACE C-18, 5 μm (4.6 mm x 250 mm)

Column oven: 40 °C

Mobile Phase: Acetonitrile/Milli Q water (20:80 v/v)

A = Milli Q water; B = Acetonitrile

0-12 min 20% B; 12-17 min 20-80% B; 17-23 min 80% B; 23-24 min 80-20% B;

24-45 min 20% B.

Flow rate: 0.8 mL/min

Detector: Vanquish PDA operating at 201 nm

Relative peak area of the main component:

Initial analysis: Mean = 98.5%, s = 0.1% (5 ampoules in duplicate, June 2024)

HPLC: Instrument: Thermo Scientific UltiMate 3000 OR Shimadzu Binary pump LC-20AB, SIL-20 A HT

Column: ACE C-18, 5 μm (4.6 mm x 250 mm)

Column oven: 40 °C

Mobile Phase: Acetonitrile/Milli Q water (20:80 v/v) A = Milli Q water; B = Acetonitrile

0-18 min 20% B; 18-23 min 20-80% B; 23-28 min 80%B; 28-29 min 80-20%B;

29-35min 20%B.

Flow rate: 0.8 mL/min

Detector: RS Diode Array or Shimadzu SPD-M20A PDA operating at 201 nm

Relative peak area of the main component:

Initial analysis: Mean = 99.0%, s = 0.01% (7 ampoules in duplicate, August 2022) Re-analysis: Mean = 97.4%, s = 0.1% (5 ampoules in duplicate, June 2023)

The following analytical data was obtained on the bulk material subsequently used in the preparation of the ampoules.

The identity was confirmed by a range of spectroscopic techniques, NMR, IR and MS. The purity value was obtained by mass balance from a combination of traditional analytical techniques, including UHPLC-UV detection, thermogravimetric analysis, Karl Fischer analysis, and ¹H NMR spectroscopy. The purity value is calculated as per Equation 1.

Purity = $(100 \% - I_{ORG}) \times (100 \% - I_{VOL} - I_{NVR})$

Equation 1

Iorg = Organic impurities of related structure, IvoL = volatile impurities, InvR = non-volatile residue.

Supporting evidence is provided by elemental microanalysis.

HPLC: Instrument: Thermo Scientific UltiMate 3000

Column: ACE C-18, 5 μm (4.6 mm x 250 mm)

Column oven: 40 °C

Mobile Phase: Acetonitrile/Milli Q water (20:80 v/v)

A = Milli Q water; B = Acetonitrile

0-18 min 20% B; 18-23 min 20-80% B; 23-28 min 80%B; 28-29 min 80-20%B;

29-35min 20%B.

Flow rate: 0.8 mL/min

Detector: RS Diode Array at 201 nm

Relative peak area of the main component:

Initial analysis: Mean = 98.9%, s = 0.03% (7 sub samples in duplicate, August 2022)

Karl Fischer analysis: Moisture content 0.1% mass fraction (August 2022)

Thermogravimetric analysis: Volatiles content 0.3% and non-volatile residue < 0.2% mass fraction (November 1999

& October 2005)

Ampouled 18 August 2022

Spectroscopic and other characterisation data

GC-MS: Tetra-TMS derivative:

Instrument: HP 6890/5973

Column: HP Ultra 2, 17 m x 0.22 mm I.D. x 0.11 μm

Program: 170 °C (0.5 min), 3 °C/min to 234 °C, 10 °C/min to 265 °C (3 min)

Injector: 280 °C
Split ratio: 20/1
Transfer line temp: 300 °C
Carrier: Helium
Scan range: 50-550 m/z

The retention time of tetra-TMS derivative is reported with the major peaks in the mass spectra. The latter are

reported as mass/charge ratios and (in brackets) as a percentage relative to the base peak.

Tetra-TMS (13.5 min): 642 (M+, 2), 552 (7), 462 (4), 357 (3), 143 (86), 73 (80) m/z

TLC: Conditions: Kieselgel 60F₂₅₄. Ethyl acetate

Single spot observed, $R_f = 0.3$

IR: Instrument: Perkin-Elmer FT-IR

Range: 4000-400 cm⁻¹, Nujol mull

Peaks: 3592, 3328, 2357, 1454, 1377, 1266, 994, 934 cm⁻¹

¹H NMR: Instrument: Bruker Avance III-500

Field strength: 500 MHz

Solvent: DMSO-d₆ (2.50 ppm)

Spectral data: δ 1.00 (3H, s), 1.05, 1.42 (3H, s), 1.51 (3H, s), 3.89 (1H, br s), 3.99 (1H, br s), 4.1 (1H,

br d), 5.50 (1H, d) ppm

Signals consistent with the 3β-hydroxy isomer are observed in the 1H NMR spectrum

at a relative mass fraction of 1%.

¹³C NMR: Instrument: Bruker Avance III-500

Field strength: 126 MHz

Solvent: DMSO- d_6 (39.52 ppm)

 $Spectral\ data: \qquad \qquad \delta\ 16.3,\ 23.4,\ 25.2,\ 25.4,\ 26.7,\ 27.9,\ 31.2\ (d),\ 34.4,\ 37.0,\ 38.5,\ 42.1\ (d),\ 44.3,\ 45.2,\ 62.2,\ 44.3,\ 45.2,\ 62$

69.7 (d), 71.8, 80.4, 101.0 (d), 127.5, 146.5 ppm

Melting point: 201-203 °C

Microanalysis: Found: C = 67.7%, H = 8.8%

Calculated: C = 67.8%, H = 8.8% (Calculated for $C_{20}H_{31}FO_4$)